

according to Regulation (EC) No. 1907/2006

Ref. 130000005783/D

Rev. no. 1.4

Revision Date 09.06.2017

Print Date 23.06.2017

StoLevell Calce FS

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

Trade name StoLevell Calce FS

1.2 Relevant identified uses

of the substance or mixture and uses advised against

Knife filler/ Surfacer

Uses advised against This information is not available.

1.3 Details of the supplier of

the safety data sheet

Sto SE & Co. KGaA Ehrenbachstr. 1 D - 79780 Stühlingen Telephone: +49 7744 57-0 Telefax: +49 7744 57 -2178

infoservice@sto.com Sto SE & Co. KGaA

E-mail address of person responsible for the SDS

TIQ Quality Management Department

European Union e.volz@sto.com

1.4 Emergency telephone number European Union

Phone: +44 (0)1235 239 670

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Serious eye damage, Category 1 H318: Causes serious eye damage.

Skin irritation, Category 2 H315: Causes skin irritation.

Specific target organ toxicity - single exposure, Category 3,

Respiratory system

H335: May cause respiratory irritation.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)



according to Regulation (EC) No. 1907/2006

StoLevell Calce FS

Hazard pictograms





Signal word Danger

Hazard statements H315 Causes skin irritation.

> H318 Causes serious eye damage. H335 May cause respiratory irritation.

Precautionary statements P102 Keep out of reach of children.

Prevention:

P261 Avoid breathing dust.

P271 Use only outdoors or in a well-ventilated area. P280 Wear protective gloves/ protective clothing/ eye

protection/ face protection.

Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for

several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/ attention.

P315 P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

If skin irritation occurs: Get medical advice/

P332 + P313 attention.

P362 + P364 Take off contaminated clothing and wash it

before reuse.

P304 + P340 IF INHALED: Remove person to fresh air and

keep comfortable for breathing.

Hazardous components which must be listed on the label:

portland cement

2.3 Other hazards

Mortar/render has an alkaline reaction with water. Therefore protect your skin and eyes. Wash thoroughly with water in case of skin contact. Immediately consult a doctor in case of contact with eyes! Risk of infection of the lung after prolonged inhalation of dust particles.

Results of PBT and vPvB assessment

Not applicable

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2 Mixtures

Chemical nature Cementitious and calcareous factory-made mortar.

Hazardous components

Chemical name	CAS-No. EC-No. Registration number	Classification (REGULATION (EC) No 1272/2008)	Concentration (% w/w)
portland cement	65997-15-1	Eye Dam.1; H318 STOT SE3; H335	≤ 20



according to Regulation (EC) No. 1907/2006

StoLevell Calce FS

	266-043-4	Skin Irrit.2; H315	
calcium hydroxide	1305-62-0 215-137-3 01-2119475151-45-XXXX	Eye Dam.1; H318 STOT SE3; H335 Skin Irrit.2; H315	≥3-<5
Substances with a workpla	ce exposure limit :	•	
Quartz (particle of sand < 12 µm less than 1 %)	14808-60-7 238-878-4	WEL substance, Not a dangerous substance according to GHS.	≥ 30 - < 50

For explanation of abbreviations see section 16.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures

Inhalation Move to fresh air.

If symptoms persist, call a physician.

Skin contact Take off contaminated clothing and shoes immediately.

Wash off immediately with soap and plenty of water.

If symptoms persist, call a physician.

Wash clothing before reuse.

Eye contact In case of eye contact, remove contact lens and rinse immediately with

plenty of water, also under the eyelids, for at least 15 minutes. If possible, use isotonic eye rinse solution (e.g. 0,9% NaCl).

Do not rub affected area. Call a physician immediately.

Ingestion Rinse mouth.

If conscious, drink plenty of water.

Do NOT induce vomiting. Obtain medical attention.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms No information available.

Treatment Treat symptomatically.

No information available.

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media

Use extinguishing measures that are appropriate to local circumstances

and the surrounding environment.

Unsuitable extinguishing Not applicable



according to Regulation (EC) No. 1907/2006

StoLevell Calce FS

media

5.2 Special hazards arising from the substance or

mixture

In set state, the product itself is classified as non-combustible in

accordance with EN 13501-1.

The product is neither explosive nor combustible and is also not oxidising

in relation to other materials.

5.3 Advice for firefighters No special measures required.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

6.2 Environmental precautions

Avoid dust formation.

Use respiratory protective device against the effects of dust.

The product should not be allowed to enter drains, water courses or the

If the product contaminates rivers and lakes or drains inform respective

authorities.

6.3 Methods and material for containment and cleaning

up

Use mechanical handling equipment.

Moisten and remove.

Avoid whirling up dust - vacuum-clean rooms instead of sweeping.

Do not use compressed air for cleaning purposes.

Dispose of contaminated material as waste according to item 13.

Clean contaminated surface thoroughly.

6.4 Reference to other

sections

Refer to protective measures listed in sections 7 and 8.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling

Advice on safe handling Avoid dust formation.

When handling sacked goods and using open mixing containers, first pour in water, then carefully allow the dry mortar to run in. Keep fall height low.

Start up mixer slowly.

Do not compress empty sacks, e.g. in a larger sack.

Large loads of over 25 kg should be moved not by hand but with the aid of mechanical equipment only. Depending on the employee's age, gender and constitution and the frequency with which loads are lifted and carried,

they may also induce a high level of strain at lower weights.

Do not kneel in fresh product while working.

Provide sufficient air exchange and/or exhaust in work rooms.

Do not re-use empty containers.

Hygiene measures When using do not eat, drink or smoke.

Wash hands before breaks and at the end of workday.

Avoid contact with the skin and the eyes.

Remove and wash contaminated clothing before re-use.



according to Regulation (EC) No. 1907/2006

StoLevell Calce FS

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

Store in original container. Keep in a dry place.

Advice on protection against

fire and explosion

When exposed to high temperatures may produce hazardous

decomposition products such as carbon monoxide and dioxide, fumes.

Further information on storage

conditions

Protect from humidity and water.

Manufacturer's notes on storage conditions and product life must be

observed.

Advice on common storage

No materials to be especially mentioned.

7.3 Specific end use(s)

For further information, see also Technical Data Sheet for the product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Quartz (particle of sand < 12 µm less than 1 %)		14808-60-7	
Additional advice:	Longer and / or strong inhalation of alveolae penetrating fine quartz dust can lead to pneumoconiosis, also know as silicosis. The effect of quartz dust (including cristobalite and tridymite) is a long-term effect and largely depends on the dose of dust, which is determined by the average dust concentration over a long period of tim (respirable fraction).	ne	
calcium hydroxide		1305-62-0	
91/322/EEC	Limit Value - eight hours		5 mg/m³
Additional advice:	Existing scientific data on health effects appear to be particularly limited Indicative	e	

The lists that were valid during the creation were used as basis.

8.2 Exposure controls

Appropriate engineering controls

To avoid dust formation, closed systems (e.g. silo with feed system), local extractors or other technical control devices should be used, e.g. plastering machines or continuous mixers with special auxiliary equipment for collecting dust.

Washing facilities / water for rinsing eyes and skin should be available. Maintain air concentrations below occupational exposure standards.

Individual protection measures, such as personal protective equipment

a) Eye/face protection Safety glasses with side-shields conforming to EN166



according to Regulation (EC) No. 1907/2006

StoLevell Calce FS

b) Skin protection Hand protection

Nitrile coated cotton gloves Break through time: 480 min

Minimum thickness: 0,8 mm

Protective gloves complying with EN 388.

e.g. KCL 102 Sahara® Top (Kächele-Cama-Latex GmbH, Hotline:

0049(0)6659-87-300, kcl-uk@kcl.de), or equivalent.

Gloves to afford protection from chemicals (cat. III) are not required.

Soaked gloves should be changed. Keep replacement gloves available.

After washing hands, replenish lost skin oil by means of oily skin

ointment.

Take note of the information given by the producer concerning

permeability and break through times, and of special workplace conditions

(mechanical strain, duration of contact).

The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the

other.

Body Protection Long sleeved clothing

c) Respiratory protection Avoid inhalation of particles.

Mixing and transferring dry mortars in open systems:

Compliance with the maximum permissible levels at the workplace is to be ensured by effective dust control measures, e.g. local extraction devices. Where this is not possible, particle-filtering half masks of type

FFP2 (tested in accordance with EN 149) are to be used.

Manual working of ready-to-use mortar: No respiratory protection

necessary.

Machining of mortar: No respiratory protection necessary.

Environmental exposure controls

General advice

The product should not be allowed to enter drains, water courses or

the soil.

If the product contaminates rivers and lakes or drains inform

respective authorities.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance powder

Colour white
Odour odourless

Odour Threshold No data available

pH > 11,5, 20 °C, (aqueous suspension)



according to Regulation (EC) No. 1907/2006

StoLevell Calce FS

Melting point/freezing point Not applicable
Initial boiling point and boiling not applicable

range

Flash point not applicable

Evaporation rate not applicable

Flammability (solid, gas)

The product is not flammable.

Lower explosion limit not applicable
Upper explosion limit not applicable
Vapour pressure No data available
Vapour density not applicable
Density not applicable
Solubility(ies)(Water) slightly soluble
Partition coefficient: n- not determined

octanol/water

Auto-ignition temperature not auto-flammable

Decomposition temperature No data available

Viscosity, dynamic not applicable

Explosive properties Not explosive
Oxidizing properties Not applicable

9.2 Other information

Bulk density ca. 730 kg/m³, 20 °C

Flow time not applicable

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions This information is not available.

10.4 Conditions to avoid

Conditions to avoid Avoid exposure to water and moisture during storage (moisture leads

to an alkaline reaction which causes the mixture to harden).



according to Regulation (EC) No. 1907/2006

StoLevell Calce FS

10.5 Incompatible materials

Materials to avoid Reacts exothermically with acids; the moist product is alkaline and

reacts with acids, ammonium salts and base metals, e.g. aluminium, zinc, brass. The reaction with base metals produces hydrogen.

10.6 Hazardous decomposition products

Hazardous decomposition

products

No decomposition if stored and applied as directed.

Decomposition temperature No data available

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Product

Acute oral toxicity Based on available data, the classification criteria are not met.

Acute inhalation toxicity Based on available data, the classification criteria are not met.

Acute dermal toxicity Based on available data, the classification criteria are not met.

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye irritation Causes serious eye damage.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Genotoxicity in vitro Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Effects on fertility Based on available data, the classification criteria are not met.

Developmental Toxicity Based on available data, the classification criteria are not met.



according to Regulation (EC) No. 1907/2006

StoLevell Calce FS

STOT - single exposure May cause respiratory irritation.

STOT - repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

Human experience Cement may exacerbate existing illnesses of the skin, eyes and

respiratory passages, e.g. in case of pulmonary emphysema or

asthma.

Further information The product itself has not been tested. The mixture is classified in

accordance with Annex I to EC Directive 1272/2008. (See sections 2

and 3 for details).

Components: portland cement

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye damage.

STOT - single exposure

Exposure routes: Inhalation May cause respiratory irritation.

calcium hydroxide :

Skin corrosion/irritation

Species: Rabbit

Causes skin irritation.

Serious eye damage/eye irritation

Species: Rabbit

Causes serious eye damage.

STOT - single exposure

Exposure routes: Inhalation May cause respiratory irritation.



according to Regulation (EC) No. 1907/2006

StoLevell Calce FS

SECTION 12: ECOLOGICAL INFORMATION

12.1 Toxicity

Product:

Toxicity to fish No data available

12.2 Persistence and degradability

Product:

Biodegradability No data available

12.3 Bioaccumulative potential

Product:

Bioaccumulation No data available

12.4 Mobility in soil

Product:

Mobility Not applicable

12.5 Results of PBT and vPvB assessment

Product:

Assessment This substance/mixture contains no components considered to be

either persistent, bioaccumulative and toxic (PBT), or very persistent

and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

Product:

larger quantities are released into water resulting in a change of the pH-value. Do not flush into surface water or sanitary sewer system.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Product The user is responsible for proper coding and marking of any waste.

When used as recommended, the waste code can be selected according

to the code of the European Waste Catalogue (EWC).

Opened and left-over materials can be used later. Only material no longer

suitable for use should be mixed with water and allowed to harden.



according to Regulation (EC) No. 1907/2006

StoLevell Calce FS

Hardened product residues may be disposed of as industrial waste or

building rubble under waste codes 17 01 01 or 10 13 14. Unhardened product residues should be disposed of under the

recommended waste code number.

Contaminated packaging Packaging that is not properly emptied must be disposed of as the

unused product.

Empty packaging should be recycled through disposal systems.

Waste key for the unused

product

17 09 03*: other construction and demolition waste (including mixed

waste) containing hazardous substances

: (*) hazardous waste in terms of the European directive 91/689/EEC

SECTION 14: TRANSPORT INFORMATION

14.1 UN number

Not regulated as a dangerous good

14.2 UN proper shipping name

Not regulated as a dangerous good

14.3 Transport hazard class(es)

Not regulated as a dangerous good

14.4 Packing group

Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Remarks This information is not available.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Remarks Not applicable

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2004/42/EC



according to Regulation (EC) No. 1907/2006

StoLevell Calce FS

does not fall under Directive 2004/42/EC

Regulation (EC) No 649/2012 of : Not applicable the European Parliament and the Council concerning the export and import of dangerous chemicals

Other regulations Comply with the statutory regulations on health and safety at work.

15.2 Chemical safety assessment

This information is not available.

SECTION 16: OTHER INFORMATION

Changes from the previous version are indicated by markings in the left-hand margin. The information in this Safety Data Sheet corresponds to our present state of knowledge and conforms to both national and EU legislation. The user's working conditions are, however, beyond our knowledge and control. The user is responsible for complying with all necessary legal requirements. The information in this Safety Data Sheet describes the safety requirements of our product and does not constitute any assurance of product properties.

Full text of H-Statements

H315 : Causes skin irritation.

H318 : Causes serious eye damage. H335 : May cause respiratory irritation.

Full text of other abbreviations

Eye Dam. : Serious eye damage

Skin Irrit. : Skin irritation

STOT SE : Specific target organ toxicity - single exposure

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road: AICS - Australian Inventory of Chemical Substances: ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO -International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and



according to Regulation (EC) No. 1907/2006

StoLevell Calce FS

Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Other information The assessment was carried out in accordance with Article 6 (5) and

Appendix I of EC Directive no. 1272/2008.

It is possible in the interim period that you may find different markings on packaging compared to the Material Safety Data Sheet until stocks have been used up. We ask for your understanding in this

matter.

Department issuing MSDS Department TIQS Sto SE & Co. KGaA Stühlingen, Germany

e.volz@sto.com

Product code

REG_EU / EN

PROD2122



according to Regulation (EC) No. 1907/2006

StoLevell Calce FS